

NAME **Kemp Anderson**
 COUNTRY **USA**
 RACE **US Indoor Champs**
 TRACK **Embassy Suites, Independence OH**

DATE **November 27-30, 2025** TEMPERATURE AIR / TRACK **70F °C / 70F °C**
 ASPHALT ☐ OUTDOOR ☐ INDOOR ☐ CARPET ☒
 TRACK CONDITION BUMPY ☐ FLAT ☐ TECHNICAL ☐ MIXED ☒ FAST ☐
 TRACTION LOW ☐ MEDIUM ☒ HIGH ☐

STEERING BLOCKS
 AT1204-X ☒
 AT1204-ZTX ☐
 OTHER _____

STEERING HUB POSTS
 ST1208-C4S ☐ ST1208-C4AL ☐
 ST1208-C5S ☐ ST1208-C5AL ☐
 ST1208-C6S ☒ ST1208-C6AL ☐
 OTHER _____

SUSPENSION PLATE
 C1205-X ☐
 C1205-ZT ☐
 C1205-X-1.5 ☒
 C1205-6.0 ☐
 OTHER _____

SERVO PLATE
 C1201-X ☐
 C1201-ZT ☐
 C1201 ☐
 OTHER **C1201X-3**

FOAM BUMPER
 P1215 ☐
 OTHER **MXLR +3mm**

BUMPSTEER SHIMS **3** mm

JOINT SET
 LRC ☒ HRC ☐
 ELRC ☐ EHRC ☐

REAR SPRING
 SPR12XR-C0.8 ☐
 SPR12XR-C1.0 ☒
 SPR12XR-C1.2 ☐
 OTHER **Long spring**

JOINT SPACER
 FRONT **0** mm
 REAR **0.5** mm

CAMBER
 0.75 deg ☐
 1.00 deg ☐
 1.25 deg ☐
 1.50 deg ☐
 1.75 deg ☒
 OTHER _____

DAMPER OIL **80k**

DAMPER STD ☒ HW ☐

OR14V ☒ YES ☐ NO

RIDE HEIGHT SPACERS **0.25** mm

SIDE SPRINGS
 SPR12XS-C0.8 ☐
 SPR12XS-C1.0 ☐
 SPR12XS-C1.2 ☐
 OTHER **SPR12S0.5**

FRONT HUBS SETUP
 SPR12F C0.7 ☒ C0.9 ☐ C1.1 ☐
 C1.3 ☐ C1.7 ☐

TOP SHIMS **.2** mm **7** pcs
BOTTOM SHIMS **.2** mm **3** pcs
KINGPIN EXTENSION _____ mm
O-RINGS 0pcs ☒ 1pcs ☐ 2pcs ☐
O-RING TYPE _____
GREASE **15K kyosho**

SIDE SPRINGS SHIMS **1.0** mm
SIDE SPRINGS GAP **0** mm

REAR AXLE
 SSS SPOOL ☒ BALL DIFF ☐ GEAR DIFF ☐
 CS-1 SPOOL ☐ LOOSE ☐ BRAND _____
 CARBON ☐ MEDIUM ☐ OIL _____
 STEEL ☐ TIGHT ☐

FRONT RIDE HEIGHT (FRH)	3.3 mm	FRONT DROOP (FD)	0.6 mm
REAR RIDE HEIGHT (RRH)	3.5 mm	REAR DOWNSTOP (RD)	1.80 mm
GAP UNDER DAMPER (GUD)	3.8 mm	TRACK WIDTH	
DOWNSTOP NUT GAP (DNG)	1.2 mm	FRONT	168 mm
SPRING ROD HEIGHT (SRH)	0.7 mm	REAR	171 mm

TIRES	FRONT	REAR		
BRAND	Jaco	Jaco		
TYPE	Mint	Mint		
DIAMETER	39.6 mm	40.4 mm	FRONT	REAR
ADDITIVE	Sxt 3.0	Sxt 3.0	TIME 15 min	TIME 30 min

BATTERY	Team EAM 8800	SERVO	Sanwa PGS-HX
BATTERY PLUGS	FRONT ☒ BACK ☐	SERVO SAVER	Xray hard
SERVO POSITION	LEFT ☐ RIGHT ☒	SHIMS ON SERVO SAVER	1.5 mm
ESC POSITION	LEFT ☒ RIGHT ☐	TOE OUT	1 total °
		STEER. TRAVEL	IN 26 ° OUT °

MOTOR	Hobbywing 3.5t	TOTAL WEIGHT	734 g
SPUR 88 PINION 24 ROLLOUT 34.61		F/R WEIGHT DISTRIBUTION	%
ESC	Hobbywing 1s HD	RECEIVER	Sanwa RX-493i
ESC SETTING	Boosted	RADIO	Sanwa M17s
BODY	Montech M20	REAR BODY HEIGHT (SIDE DAMS)	81 mm
BEST LAP TIME	8.4	QUALIF. / FINAL POSITION	1 / 1

COMMENTS:

MXLR electronics tray
1 turn of preload on each side spring before setting tweak
Double sauce rears